

Commercial/Industrial COLOR CHART



SIGNATURE[®] 200 Standard Colors SILICONIZED POLYESTER



HAWAIIAN BLUE
SR.32 SRI 35



CRIMSON RED†
SR.38 SRI 42



FERN GREEN
SR.28 SRI 29



BURNISHED SLATE
SR.28 SRI 29



ASH GRAY
SR.48 SRI 56



SADDLE TAN
SR.48 SRI 56



DESERT SAND
SR.42 SRI 48



KOKO BROWN
SR.28 SRI 29



CHARCOAL GRAY
SR.28 SRI 29



POLAR WHITE
SR.58 SRI 69



RUSTIC RED
SR.36 SRI 40



LIGHT STONE
SR.50 SRI 58



GALLERY BLUE
SR.28 SRI 29



SOLAR WHITE *
SR.70 SRI 85

SIGNATURE[®] 300 Premium Colors KYNAR 500[®], HYLAR 5000[®]

Additional costs apply for Signature 300 finishes.



MEDIUM BRONZE
SR.33 SRI 36



SNOW WHITE
SR.65 SRI 79



SLATE GRAY
SR.37 SRI 41



ALMOND
SR.63 SRI 76



CLASSIC GREEN
SR.28 SRI 29




BROWNSTONE
SR.47 SRI 54



SCARLET RED
SR.42 SRI 47



HARBOR BLUE
SR.28 SRI 29



BONE WHITE *
SR.70 SRI 85

Commercial/Industrial Panel Profiles

What is Solar Reflectivity (SR)?

Solar reflectivity or reflectance is the ability of a material to reflect solar energy from its surface back into the atmosphere. The SR value is a number from 0 to 1.0. A value of 0 indicates that the material absorbs all solar energy and a value of 1.0 indicates total reflectance. Energy Star requires a SR value of 0.25 or higher for steep slope (above 2:12) roofing and a SR value of 0.65 or higher for low slope (2:12 or less) roofing. For more information, please go to www.energystar.gov.

What is Solar Reflectivity Index (SRI)?

The SRI is used to determine compliance with LEED requirements and is calculated according to ASTM E 1980 using values for reflectance and emissivity. Emissivity is a material's ability to release absorbed energy. To meet LEED requirements, a roofing material must have a SRI of 29 or higher for steep slope (above 2:12) roofing and a SRI value of 78 or higher for low slope (2:12 or less) roofing. For more information, please go to www.usgbc.org.



SIGNATURE® 200 - SILICONIZED POLYESTER

	SR #	SRI #
HAWAIIAN BLUE	.32	35
CRIMSON RED	.38	42
FERN GREEN	.28	29
BURNISHED SLATE	.28	29
ASH GRAY	.48	56
SADDLE TAN	.48	56
DESERT SAND	.42	48
KOKO BROWN	.28	29
CHARCOAL GRAY	.28	29
POLAR WHITE	.58	69
RUSTIC RED	.36	40
LIGHT STONE	.50	58
GALLERY BLUE	.28	29
SOLAR WHITE	.70	85

SIGNATURE® 300 - KYNAR 500® / HYLAR 5000®

	SR #	SRI #
MEDIUM BRONZE	.33	36
SNOW WHITE	.65	79
SLATE GRAY	.37	41
ALMOND	.63	76
CLASSIC GREEN	.28	29
BROWNSTONE	.47	54
SCARLET RED	.42	47
HARBOR BLUE	.28	29
BONE WHITE	.70	85

Profile	SIGNATURE® 200								SIGNATURE® 300				
	Panel	29 GAUGE		26 GAUGE		24 GAUGE		22 GAUGE		26 GAUGE		22 GAUGE	
		Galvalume Plus*	Sig 200 (Interior liner only)	Galvalume Plus*	Sig 200	Galvalume Plus*	Sig 200	Galvalume Plus*	Sig 200	Galvalume Plus*	Sig 300	Galvalume Plus*	Galvalume Plus*
 "PBR" PANEL	PBR	●	■	●		■	■	■	■	●	●	●	●
 "PBU" PANEL	PBU	●	■	●		■	■	■	■	●	●	●	●
 "PBC" PANEL	PBC	●	■	●		■	■	■	■				
 "PBD" PANEL	PBD	●	■	●		■	■	■	■				
 "PBA" PANEL	PBA	●	■	●		■	■	■	■	●	●	●	●

● Available in any quantity ■ May require minimum quantity